

AMENDMENTS TO THE SPECIFICATION

Please add the following paragraph after paragraph 0007 and before paragraph 0008:

-- FIG. 2 shows an assembled side view of the card fixture system of FIG. 1, in accordance with an embodiment of the invention. --

Please amend paragraph 0012 as indicated below:

-- FIG. 2 is a side view of the computer system shown in the exploded assembly view of FIG. 1, illustrating the installation of a card 2 within a computer chassis 1. To install a card 2 and secure it within the chassis 1, according to one embodiment, a card 2 is installed into a slot of the motherboard so that the extension 31 of the bracket 31 protrudes out of the chassis 1 through the window 31. Before the card 2 is installed, however, it may be necessary to remove any protecting covers that are often found over openings 11 in a standard computer chassis 1. When installed, a lower end 32 ~~the lower ends~~ of the bracket 3 may stick out of the bottom ~~opening openings~~ 12 of the chassis 1, as illustrated in FIG. 2, which helps to secure the card 2. Then, the clamp 4 is installed over the window, with its outward folds 42 matching the extension 31 of the bracket 3. The clamp 4 is fixed in that position by screws or other fasteners through the holes 41 and the lock holes 14. In this way, the clamp 4 secures the card 2 in place by securing its bracket 3, while the card 2 may be further secured at the opposite end 32 of its bracket 3 by the lower openings 12 of the chassis 1. --